

# SERIES 9900 • *Ultima* Standard Style Vinyl Sliding Door

07/06

## PRODUCT INFORMATION SHEET

Series 9900 Nail-On Frame • Series 9990 Retro-Fit Frame  
Series 9950 Block Frame

## FEATURES

- Available in White or Almond color.
- Artisan Sculpted and uniquely detailed exterior frame.
- Overall frame depth is 5-1/2"
- Optional 4-1/2" French Style panels are available (Series 9901/9991).
- 7/8" Insulated Glass featuring Intercept™ Warm Edge Technology.
- Thermal ratings as tested with **CLIMATE SHIELD™** High Performance Low-E glazing: U-Value = .34 and SHCG = .36 (See *Thermal & Optical Ratings* page for more info).
- Tested to NFRC 100-97 and AAMA/NWDA 101/I.S. 2-97 C-30.
- Operating panel rolls on a stainless steel track cap, which is mounted on a heavy duty aluminum track.
- Adjustable, tandem ball bearing rollers are used for ease of operation.
- Doors are shipped with frames fully assembled, frame and panel corners are fusion welded.
- Nail-on fins are an integral part of the frame at the head and jambs and are set back 7/8" from the exterior edge of the frame.
- Heavy-duty fin seal weather stripping is used. Double weather stripping at the sill ensures a smoother rolling action.
- Interlocks and lock stiles are reinforced with aluminum for maximum strength.
- Heavy-duty aluminum handle featuring a crescent pull is standard. Upgrades include a brite brass handle.
- Key locks are available.
- The Prestige heavy-duty extruded screen with steel rollers is standard.
- Doors are field reversible.
- Net frame sizes:
  - 2 Panel Units - callout minus 1/2" width and 1/4" height
  - 3 Panel Units - callout plus 1/8" width and minus 1/4" height
  - 4 Panel Units (OXXO) - callout minus 2-7/16" width and minus 1/4" height
  - 4 Panel Units (XOOX) - callout minus 1-15/16" width and minus 1/4" height