

SERIES 5300 • *Ultima* Vinyl Awning Window

06/06

PRODUCT INFORMATION SHEET

Series 5300 Nail-On Frame • Series 5390 Retro-Fit Frame
Series 5350 Block Frame

FEATURES

- Artisan sculptured and uniquely detailed exterior perimeter frame.
- Heavy-duty 3-1/4" frame with fusion welded corners.
- Windows meet and exceeds AAMA/NWWDA 101/I.S. 2-97 specifications for residential rating C-30 (8030 AO).
- 3/4" Insulated Glass with Intercept™ Warm Edge Technology. Single glaze also available.
- Surpasses California Model Building Security Ordinance for forced entry requirements.
- Truth hardware with swing cam latch are installed for sure fit and operation. Stainless steel hardware is an available option.
- Thermal ratings as tested with CLIMATE SHIELD™ High Performance Low-E glazing: U-Value = .33 and SHCG = .23 (See *Thermal & Optical Ratings* page for more info).
- Screens are mounted on the inside of the window, with special molded screen corners, concealing corner clips.
- Continuous single finger soft vinyl weather stripping around the frame and vent panel insure air tightness.
- Special sizes upon request.
- Net frame sizes for:
 - Nail-on frame - call out minus 3/8" width and 3/8" height.
 - Block frame - call out minus 1/8" width and 3/8" height.
- Available in White or Almond color.
- Nail-on frame has a 1-1/8" long, integral, prepunched nail fin located 1" from the exterior.

Configuration Available:

A	=	Single Awning
AA	=	Double Awning
AO/OA	=	Single Awning with Fixed Bottom
TA, TAA, BA, BAA	=	1/2 Awning, 1/2 Fixed
TA1, TAA1, BA1, BA1	=	1/6 High Awning Balance in Fixed
TA2, TAA2, BA2, BA2	=	2/0 High Awning Balance in Fixed
TA3, TAA3, BA3, BA3	=	3/0 High Awning Balance in Fixed