

THERMAL PERFORMANCE SUMMARY REPORT

All numbers reflect U-Values

This is for private use and reference only; publication of this information is limited to customers of Atrium Windows & Doors only. All other uses and distribution is prohibited.

This summary is to be used as a reference.

Series/Model	Clear(SSB)	Clear/Low-E (SSB)	Clear/Low-E w/Argon (SSB)
8100 PW/HR/FR/OC/SS	0.45	0.31	0.27
8100 SH	0.49	0.36	0.33
8300 PW/HR/FR/OC/SS	0.45	0.31	0.27
8300 DH	0.48	0.35	0.32
8500/8700 PW/HR/FR/OC/SS	0.45	0.31	0.27
450/8500/8700 DH	0.48	0.35	0.32
100 PW/HR/FR/OC/SS	0.50	0.35	0.31
100 SH	0.51	0.38	0.33
123/124 Sliders	0.47	0.34	0.30
150/160 PW/HR/FR/OC/SS	0.47	0.33	0.30
150/160 SH	0.49	0.36	0.33
151/161 2SL/3SL	0.48	0.35	0.32
200 PW/HR/FR/OC/SS	0.45	0.31	0.27
200 SH	0.49	0.36	0.33
201 2SL/3SL Sliders	0.48	0.35	0.31
120/130/201 2SL/3SL	0.48	0.35	0.31
311/312/313/314 Patio Doors	0.48	0.34	0.33
315 PW/HR/FR /OC/SS	0.47	0.32	0.28
316 PW/HR/FR /OC/SS	0.46	0.33	0.29
450 PW/SS	0.45	0.30	0.27
451 2SL/3SL	0.47	0.34	0.30
332/333/334 Patio Door	0.48	0.34	0.33
335 Patio Door Transoms	0.47	0.33	0.29
336 Patio Door Side Lites	0.47	0.33	0.30
700/750 Casements	0.44	0.34	0.30
705/755 Awnings	0.45	0.34	0.30
700/750 PW/HR/FR/OC/SS	0.46	0.33	0.29